







Productive, low-cost and easyto-use laser printer for all your daily print needs

Outstanding office productivity

- Up to 30ppm laser printing, and as fast as 8.5 second firstpage-out keeps up with your workload.
- A 400MHz processor delivers complex pages fast.
- Two paper trays, plus an optional third tray, increases paper choice and capacity.
- Additional features such as watermarks, N up, posters, and booklets give you eye-catching, customised results.
- Connect the way you want with USB and Parallel. For multiple users, 10/100BaseT Ethernet is standard on the Phaser 3428/DN model.

Excellent value

- Affordable price lets you enhance your business potential without breaking your budget.
- Automatic two-sided printing saves time and paper:
- 1,200 image quality resolution means crisp, professional printouts, while toner saver mode will save money on less critical jobs.
- A compact design lets you put it where you need it.

Easy to use

- Installation is quick, easy and the status monitor will alert you if there are problems while printing.
- Remotely control, monitor, and diagnose your printer when connected to your network.
- Minimise supplies interaction with easy to install, high yield toner cartridges.

CONFIGURATIONS		Phaser® 3428/D	Phaser® 3428/DN
Speed		Up to 30ppm	
Duty Cycle		Up to 65,000 pages / month	
Paper Handling			
Paper Input	Standard	Bypass Tray: 50 sheets; Size: Custom sizes from 76 x 127mm to 216 x 356mm	
		Tray 1: 250 sheets, Size: Custom sizes f	rom 76 x 127mm to 216 x 356mm
	Optional	Tray 2: 250 sheets, Size: Custom sizes f	rom 76 x 127mm to 216 x 356mm
Paper Output		150 sheets (face-down)	
Automatic 2-sided printing		Standard	
Print			
First Page-Out Time		As fast as 8.5 seconds	
Print Resolution		Up to 1,200 x 1,200 Image Quality	
Processor/PDL		400MHz/PCL6	400MHz/PCL6,
			Compatible with PostScript [®] 3 [™]
Connectivity		Bi-directional Parallel, USB 2.0	Parallel, USB 2.0, Pthemet 10/100 Base TX
Memory (Std / Max)		32MB/ 288MB	64MB/ 320MB
Print Reatures		Xerox Status Monitor, Watermarks, Booklet Printing, Poster Printing, N. Up,	
		Fit to Page, Overlays, First Page Exception Page, Auto Tray Select, Toner Saver Mode	
			Embedded Web Server

SPECIFICATIONS

Device Management

Phaser 3428/D Xerox Status Monitor

Phaser 3428/DN CentreWare Internet Services, CentreWare Web, Xerox Status Monitor, Printer Settings Utility, SetIP

Print Drivers

Windows® 95/98/Me/NT® 4.0/ 2000/XP/Server™ 2003; Mac OS* 8.6-9.2/10.1-10.4; Linux®

*Phaser 3428/DNonly

Media Handling

Bypass Tray: 60gsm - 163gsm Tray 1 standard and Tray 2 optional: 60gsm - 90gsm

Media Types: Paper, Envelopes, Labels, Transparencies, Card Stock

Two-sided Printing: Sizes: A4, Letter; Legal, Polio, Oficio, 75gsm – 90gsm

Operating Environment

Temperature: 10°C – 32°C Humidity: 20% – 80%

Electrical

Power: 100V-127V, 50 / 60Hz; 220V-240V, 50/60Hz

Power Consumption: Average: 520W, Power Saver Mode: 11W, ENFRGY STAR® Compliant Sound Power Levels:

Running: 54dBA, Standby: 39dBA

Physical Dimensions (Wx Dx H)

401 x 442 x 281mm Weight: 12.2kg

Supplies

Standard Print Cartridge (CWA40715): 4,000 pages† Hgh Capacity Print Cartridge (CWA40716): 8,000 pages† Printer is shipped with standard

yield print cartridge

[†]Approximate yield. Declared yield values in accordance with ISO/IBC 19752 ISO Compliant Toner Yields.

Regulatory

FCC Part 15 Class B, Class 1 Laser Product, CE marked in accordance with Low Voltage Directive, 72 / 23 / EFC and EMC Directive 89 / 336 / EFC, CB Certified against IEC 60950

Malaysia

Fuji Xerox Co. Ltd. (994158-D) (Fuji Xerox Printers) Wisma Fuji Xerox, 1st Floor No. 10, Jalan Bersatu 13/4, 46200 Petaling Jaya, Selangor Malaysia

Tel: 03-7882 2888 Fax: 03-7882 2767

Service Hotline : 1800 88 1063 www.fxprinters.com.my











